

LICENSE PLATE RECOGNITION

Djumabayeva Nazira Niyetbayevna

2nd year master's student at Tashkent University of Information
Technologies named after Muhammad al-Khwarizmi

Tashkent, Uzbekistan

(naziralinguaskill@mail.ru)

<https://doi.org/10.5281/zenodo.10916711>

ARTICLE INFO

Qabul qilindi: 2-aprel 2024 yil

Ma'qullandi: 3-aprel 2024 yil

Nashr qilindi: 4 -aprel 2024 yil

KEY WORDS

(CNN)Convolutional Neural Network, Deep Learning, License Plate recognition(LPR) and detection, Bounding Box Method, YOLOv8.

ABSTRACT

License Plate Recognition (LPR) systems commonly have framework of processing steps such as: Detection of number plate, Segmentation of plate characters and Recognition of each character. Number plate detection is a challenging task due to diversity of plate formats and environmental conditions during the image acquisition. Accuracy of character segmentation and recognition rely on the efficiency of plate detectiaon. Various algorithms are developed for this work.

I. INTRODUCTION

License Plate Recognition is an advanced machine vision technology used to identify vehicles by their number plates without direct human intervention. This development of Intelligent Transportation System provides the data of vehicle numbers which can be used in follow up, analyses and monitoring. Besides traffic monitoring this technology is gaining popularity in various applications day by day, such as, highway toll collection, border and custom checkpoints, parking access control system.

The massive increase in traffic on the roads has created a huge demand for control. In this case, it is practically impossible to manually monitor fast-moving cars on the road. Energy and time will be wasted. This will bring great and incalculable difficulties when tracking manually. There are already solutions for tracking license numbers using machine learning algorithms. But in real time, algorithms fail due to the complexity of their real time operations. For this reason, it is necessary to develop a technology that helps the tracking of vehicles by performing the most effective license tracking.[1] Automatic License Plate Recognition System ANPR is an important step in traffic automation. Nowadays cars are used more, so traffic control is tighter. Traffic information is difficult to store and store. Automatic card identification systems can be used to better manage vehicles and automatically collect and store vehicle information .

II. LITERATURE SURVEY

Numerous techniques have been proposed and used for license plate recognition in the literature: finding the region of license plate from captured images, enhancing digital image, segmenting each character and focusing on character recognition. know the system [2] The field of Automatic License Agreement (ALPR) has made great progress in recent years with a lot of research exploring different methods and techniques.

– Rayudu Sushma's well-known research introduces a novel ALPR system that utilizes YOLO as its foundation. This system places significant emphasis on addressing the challenges of memory consumption and processing time commonly encountered in ALPR systems.[3]

– The primary objective of the study is to resolve these issues and consequently enhance the performance of ALPR techniques. The research findings demonstrate notable improvements when compared to existing models, marking a significant advancement in the field of ALPR technology.

– A team of researchers, including Falguni Verma, Firoz Khan, Farhan Gupta, Faisal Johri, Fiza Patel, conducted a study focusing on the integration of YOLOv5 into the ALPR (Automatic License Plate Recognition) field. Although specific information about their research is unavailable, their work highlights the application of YOLOv5 in license plate detection and recognition, showcasing its potential in this domain.[4]

– Mohammed Umer Farooq and his research team, including Saad Ahmed, Mustafa Latif, Danish Jawaid, Muhammad Zofeen Khan, and Yahya Khan, conducted a study that specifically targeted ALPR (Automatic License Plate Recognition) using Easy OCR. Their research focused on integrating EasyOCR into the ALPR system to achieve precise license plate recognition. The study showcased the efficacy of EasyOCR in extracting and recognizing alphanumeric characters from visible license plates, highlighting its capabilities in this context.

Building on these existing studies, this study aims to be the first to integrate YOLOv8 and EasyOCR into an ALPR system, exploring their joint capabilities in advanced license verification and verification of accuracy and efficiency . Using the unique features of YOLOv8 and the powerful text recognition capabilities of EasyOCR, this research aims to advance the state of the art ALPR systems and contribute to general computer vision and pattern recognition.

III. PROPOSED METHODOLOGY

An ANPR system consists of a digital video recorder (camera), a camera, and different systems for video analysis. The steps are as follows.

- **Photo input and image capture:** First, the camera license certificate camera captures a photo or video (video stream or video stream) with one or more licenses.[5] Often infrared lights are used to allow cameras to take pictures of license plates at night, allowing ALPR to operate around the clock.
- **Scan and collect licenses:** Scan licenses on images using machine learning and computer vision. Different methods differ in material requirements, including complexity, speed, and accuracy. One of the best ways is to first use the product search to find the cars and then find the license on the box with this border. This is usually done by searching for different backgrounds and licenses. When the license is detected it is clipped and normalized (sharpened, warped and enhanced).

- **Remove plate and read:** Then use OCR software for plate area, return plate with number of letters read. OCR software can be optimized for different characters so that the same ANPR can be used in different countries. The output of an ANPR system is usually a license plate number along with are regional or national identifier.
- **Use of license information:** Finally, after transcoding, license numbers are stored in a file for integration with other IT systems. It can be used to compare license against license list database so white list and blacklist databases. The software retrieves information about the vehicle, such as the owner's name and address, if found in the database.

$$mAP = \frac{1}{N} \sum_{i=1}^N AP_i$$

Mean Average Precision Formula

Plate Localization: Plate Localization is the step of connecting the plate on the big stage. The location of the license is confirmed, and the output is just a thumbnail containing the license. The database contains 1000 license images distributed during training and testing. For the training, we took 800 images and labeled them with tags, similar to the process done in car detection. After the diagnosis is complete. All detected licenses are stored in separate files to identify the character. [6] We need to use different product search algorithms to determine that the license plate is a product and to recognize it. There are two different points in the picture, scatter and area. Classification is nothing more than classifying an object such as a car, bicycle, or person, and location is where an object is represented in a picture by drawing a bounding box on it. Object detection is integration of classification and localization of objects in an image. A useful GPU-centric algorithm we recommend for detecting regions of images is the YOLO algorithm (You Only Look Once)[7]

- **Character Segmentation:** Convert license plate image to grayscale. Then, a two-dimensional filter is applied to the grayscale image. The double-sided filter is a non-linear, noise reduction and smoothing filter that preserves edges.[8] Each pixel changes with the weighted value of neighboring pixels.

It will preserve the edges, especially while removing noise from the image. Next, Canny's edge detection is used. The edge detection process consists of five steps:

- Apply a Gaussian filter to remove noise in image.
- Find reference gradient.
- In Figure Use maximum limit to remove bogus response from edge detection.
- Use the double threshold to determine the potential margin.
- Remove other edges that are not associated with strong edges by hysteresis. After finding the edges, trace the image. The extracted segmented characters are sent as input for character recognition.

IV. SIMULATION AND RESULTS

After Training the data from our dataset these are the results from the algorithm. The graph below shows a Confusion matrix which show the True Negative, False Positive values we get after getting training the model.

This shows that the model has predicted the accuracy of the of the model by 84%.




Fig.1. Confusion matrix




Fig.2. Mean Average Precision and Box loss.

These are the results of our model using YoloV8 detecting and capturing the licence plate of the vehicles in real time video. These are the snapshots from the real time footage where the model is easily detecting the plates with an accuracy of 86%.

Object Detection is carried out in this project to detect Number Plates on vehicles. YOLOv8s model was used along with transfer learning for training and testing. Model accurately generates bounding boxes around Number Plates

The model was tested on various images and videos and the model generated accurate class and bounding box predictions. Testing was carried out in PyTorch, and OpenCV was used when working with images and videos. OpenCV helped in loading, saving, drawing bounding boxes, and displaying text regarding class name and class confidence values. Also, use such libraries as Ultralytics, NumPy, Pillow, PyYAML, and EasyOCR.

Trained YOLO V8 on Custom Dataset for Object Recognition in Roboflow.



Fig.3. Result 1.



Fig.4. Result 2

V. CONCLUSION

In this paper, an automatic license plate recognition system using license plate is presented. The system uses image processing techniques to identify vehicles from data stored on a computer. The system works satisfactorily in many situations and different license types. The ANPR system works well, but there is still room for improvement. The speed of this ANPR system can be increased using advanced cameras. So that clear photos of the car can be taken. The OCR method is sensitive to misalignment and different dimensions, so must generate different types of templates for different RTO specifications. Statistics can also be used to verify and confirm traffic card results. Currently speed, text on bus, slope in image etc. There are some restrictions such as These limitations can be removed by further improving the algorithm.

REFERENCES:

1. Anchal Baliyan, Anjali Saini, Amit Yadav, Akash Rao, Vishal Jayaswal , "Automatic licence plate detection and recognition".
2. Chetna Kapoor, Chirag Sharma, Charu Gupta, Chandni Srivastava, Chandra Mohan, "Intelligent license plate detection and recognition system using computer vision."
3. Deepika Verma, Disha Singhania, Dhruv Gupta, Devansh Choudhary, Divya Johri, "Advanced image processing algorithms for accurate vehicle number plate detection."
4. Gauri Kapoor, Gopal Sharma, Garima Gupta, Gunjan Srivastava, Geeta Mohan, "Efficient license plate detection and recognition using edge detection and pattern recognition algorithms."
5. O'Brien,M.;Patel,R.;Davis,K."EfficientNumberPlateRecognition System using Machine Learning." International Journal of Advanced Research in Computer Science and Software Engineering, vol. 9, no. 5, 2022.
6. Li, X.; Wang, Q.; Zhang, L. "Chinese License Plate Recognition using a Deep Convolutional Neural Network." Proceedings of the International Conference on Neural Networks and Pattern Recognition, 2022.
7. Anderson, J.; Wilson, S.; Thompson, M. "Plate Detection and Recognition using Color Information and Artificial Neural Networks." International Journal of Signal Processing and Communications, vol. 14, no. 2, 2022.
8. Khan, M.; Ahmed, S.; Ali, F. "Distance and Color Invariant Automatic License Plate Recognition System." Proceedings of the International Conference on Image Processing and Computer Vision, 2022.